

Hytera 

P **XRUGGED**
PNC460 **SMART DEVICE**

DESIGNED FOR WORK EFFICIENCY



READY FOR EFFICIENCY



Android 12 OS
Simplify your workday

With the Android 12 OS, the PNC460 delivers the familiar experience and ease of use that the professionals want. More importantly, it provides an open and inclusive platform to run a wide variety of key apps, making everyday tasks easier and faster.



Hytera-developed Toolkit
Help you work better

With versatile ready-to-use Hytera-developed tools such as high beam, noise meter, gradienter, altimeter, plumb, pedometer, and protractor, the PNC460 lets you work efficiently and effortlessly.





Exceptional Durability Withstand the tough conditions

The PNC460 is perfect for professionals working in the most demanding environments. It has tough exteriors and reinforced components to survive dust, water, snow, 1.5-meter sudden drops, extreme temperatures (-20°C to +60°C), and more.



Large HD Screen View more. Do more.

As a good assistant, the PNC460 helps you work more efficiently. The stunning 5-inch screen gives you plenty of space to use multiple apps at work. Additionally, this screen is sunlight readable and sensitive enough to react the touch of gloved hands and wet fingers.



Precise Positioning Pinpoint your device and personnel

Thanks to the built-in dual-frequency GPS (L1+L5) chip, the PNC460 provides real-time, precise location for the dispatcher with the accuracy improved to 2 meters. Know where your devices are. Keep your personnel safe.

Application Scenarios



Industrial Park



Transportation



Electricity



Customs



Airport



Logistics

Specifications

Frequency Range	GSM: 900/1800 WCDMA: B1/B3/B8 TDD-LTE: B34/B38/B40 FDD-LTE: B1/B3/B7/B8/B20/B28
Operating System	Android 12
Storage	4 GB RAM + 64 GB ROM
TF Card	128 GB (max.)
Dimensions (L x W x D)	164 mm x 77 mm x 14 mm
Weight	275 g
Screen Size	5.0 inches
Screen Resolution	1920 x 1080
SIM Slots	2 x Nano-SIM
Location	GPS (L1&L5)/A-GPS/BDS/GLONASS/Galileo
Sensor	Acceleration/gyroscope/geomagnetic/opto-sensor
WLAN	2.4 GHz&5 GHz, 802.11 a/b/g/n/ac
Drop Resistance	1.5 m
NFC	Available
Interfaces	USB Type-C port 3.5 mm audio jack
Battery Capacity	4,500 mAh
Charging Interface	USB Type-C port
Speaker	3 W (max.)
Motor	Available
Cameras	Rear: 50 MP; Front: 8 MP
Video Resolution	1080p@60fps
Operating Temperature	-20°C to +60°C
Storage Temperature	-30°C to +70°C
	IEC 61000-4-2
Electro-Static Discharge (ESD)	±12 kV (air) ±6 kV (contact)
IP Rating	IP68

Accessories



Battery



Power Cord



Power Adapter



Remote-mount Earset



Wireless Ring PTT



Wireless Remote Speaker Microphone



Wireless Earpiece (with PTT)



Charger



Hytera Communications Canada

Address: 100 Leek Crescent, Richmond Hill, ON L4B 3E6

Tel: 905 305 7545

<https://www.hytera.ca>